

FEED THROUGH TERMINALS (KUT Series)

elmex "K" Series Universal (TS35mm & TS32mm) DIN Rail Mounted **Feed Through Terminals** in Polyamide 66 Housing offers the complete range suitable for all control and power applications.

The proven screw-clamp design offers high contact force and is easy to use.

The range covers terminals for conductor sizes from 0.5 sq mm to 95 sq mm.


The special foot design provides a slot for easy mounting and removal of a single terminal from a stack, using a screwdriver.







FEED THROUGH








elmex **Spring Loaded Terminals** employ compression springs below the contact clamp assembly, for better and more reliable connection for high vibration applications.

SPRING LOADED FEED THROUGH



DESCRIPTION		KUTM 2.5	KUT 2.5	KUT 4
TERMINAL PITCH		5mm (0.20 Inch)	6 mm (0.24 Inch)	6.7 mm (0.26 Inch)
HEIGHT x WIDTH in mm (Inch)		41 x 42.5 (1.60 x 1.67)	41x 42. 5 (1.61 x 1.67)	46.4 x 42.5 (1.83 x 1.67)
RATED CROSS SECTION		2.5 sq mm	2.5 sq mm	4 sq mm
CONNECTION	Flexible	0.5 sq mm - 2.5 sq mm	0.5 sq mm-2.5 sq mm	0.5 sq mm- 4 sq mm
POSSIBILITY	Rigid	0.5 sq mm - 2.5 sq mm	0.5 sq mm- 4 sq mm	0.5 sq mm- 6 sq mm
WIRE STRIPPING LENGTH		10 mm	10 mm	12 mm
TYPE OF CONNECTION		2 screw clamp & 1 tapped hole for cross connection	2 screw clamp & 1 tapped hole for cross connection	2 screw clamp & 1 tapped hole for cross connection
RATINGS	IEC 60947-7-1 	800 V/24 A/2.5 sq mm/0.5 Nm -	800 V/24A/2.5 sq mm/0.5 Nm 300 V/25 A/12-20 AWG/7 Lbln	800 V/32A/4 sq mm/0.5 Nm 600 V/35 A/10-20 AWG/7 Lbln
SCREW SIZE		M2.6	M3	M3
				
				
TERMINAL TYPE		CAT # STD. PKG. WT/STD.PKG-KG	CAT # STD. PKG. WT/STD.PKG-KG	CAT # STD. PKG. WT/STD.PKG-KG
END PLATE 		KUTM 2.5 100 0.80	KUT 2.5 100 0.92	KUT 4 100 1.27
PARTITION PLATE WITHOUT FOOT 		KPNS 100 0.24	KPNS 100 0.24	KP X 100 0.31
PARTITION PLATE WITH FOOT 		KBM 100 0.37	KBM 100 0.37	KB X 100 0.46
SUPPORT FOR PROTECTION COVER 		KBXF 100 0.54	KBXF 100 0.54	KBXF 100 0.54
PROTECTION COVER 		UHDD 100 0.80	UHDD 100 0.80	UHDD 100 0.80
END CLAMPS		PCK 3 100 7.00	PCK 3 100 7.00	PCK 100 7.00
   		SCKN 100 0.80	SCKN 100 0.80	SCKN 100 0.80
		SCUN 100 0.94	SCUN 100 0.94	SCUN 100 0.94
		SCUSL 50 0.63	SCUSL 50 0.63	SCUSL 50 0.63
		SCUDD 50 0.64	SCUDD 50 0.64	SCUDD 50 0.64
SHORTING LINK ASSEMBLY	- 2 WAY	CCLK 2.5 - 2W 100 0.27	CCLM 2.5K-2W 100 0.32	CCLA 2.5 - 2W 100 0.56
	- 3 WAY	CCLK 2.5 - 3W 100 0.41	CCLM 2.5K-3W 100 0.46	CCLA 2.5 - 3W 100 0.84
	- 4 WAY	CCLK 2.5 - 4W 50 0.26	CCLM 2.5K-4W 50 0.31	CCLA 2.5 - 4W 50 0.56
    	- 5 WAY	CCLK 2.5 - 5W 50 0.33	CCLM 2.5K-5W 50 0.38	CCLA 2.5 - 5W 50 0.69
	- 10 WAY	CCLK 2.5 - 10W 25 0.33	CCLM 2.5K-10W 25 0.38	CCLA 2.5 - 10W 25 0.69
PERMANENT SHORTING LINK	- 2 WAY	-- -- --	-- -- --	PSL 2.5 - 2W 100 0.06
	- 3 WAY	-- -- --	-- -- --	PSL 2.5 - 3W 100 0.09
	- 4 WAY	-- -- --	-- -- --	PSL 2.5 - 4W 100 0.13
    	- 5 WAY	-- -- --	-- -- --	PSL 2.5 - 5W 100 0.15
	- 10 WAY	-- -- --	-- -- --	PSL 2.5 - 10W 100 0.26
STUD FOR PERMANENT SHORTING LINK 		-- -- --	-- -- --	SSP2 5-6 100 0.27
COMB LINK	- 2 WAY	-- -- --	SLCM2.5 - 2W 100 0.20	SIC 2.5-2W 100 0.23
	- 3 WAY	-- -- --	SLCM2.5 - 3W 100 0.30	SIC 2.5-3W 100 0.33
	- 4 WAY	-- -- --	SLCM2.5 - 4W 100 0.40	SIC 2.5-4W 100 0.47
    	- 5 WAY	-- -- --	SLCM2.5 - 5W 50 0.25	SIC 2.5-5W 50 0.29
	- 10 WAY	-- -- --	SLCM2.5 -10W 50 0.50	SIC 2.5-10W 50 0.57
REMOVABLE SHORTING LINK 		-- -- --	-- -- --	RSL 2.5 100 0.05
STUD FOR REMOVABLE SHORTING LINK 		-- -- --	-- -- --	LSR2 5-6 100 0.31
MARKING LABEL 	1 2 3 4 5 6 7 8 9 10	KN 5 100 Strips 0.07	Label KN 5.5 100 Strips 0.08	Label KN 6.5 100 Strips 0.10
WARNING LABEL 		-- -- --	-- -- --	WL 2.5 100 0.31
GROUP MARKING CARRIER	 	SCKNMLH 50 0.55	SCKNMLH 50 0.55	SCKNMLH 50 0.55
		SCUNMLH 50 0.60	SCUNMLH 50 0.60	SCUNMLH 50 0.60
COLOUR:   GREY, KHAKHI		KUTM2.5(G), KUTM2.5(K)	KUT2.5(G), KUT2.5(K)	KUT4(G), KUT4(K)
  RED, YELLOW, BLUE		KUTM2.5(R), KUTM2.5(Y), KUTM2.5(B)	KUT2.5(R), KUT2.5(Y), KUT2.5(B)	KUT4(R), KUT4(Y), KUT4(B)
  BLACK, GREEN		KUTM2.5(BL), KUTM2.5(GR)	KUT2.5(BL), KUT2.5(GR)	KUT4(BL), KUT4(GR)
MOUNTING CHANNEL		CHS 3/5/10 100/100/50 22/37/36	CHS 3/5/10 100/100/50 22/37/36	CHS 3/5/10 100/100/50 22/37/36
STANDARD LENGTHS 300MM, 500MM, 1000MM		CHK 3/5/10 100/100/100 11/19/36	CHK 3/5/10 100/100/100 11/19/36	CHK 3/5/10 100/100/100 11/19/36
		CHKS 3/5/10 100/100/100 11/17/34	CHKS 3/5/10 100/100/100 11/17/34	CHKS 3/5/10 100/100/100 11/17/34
		CHKDS 10 50 34.50	CHKDS 10 50 34.50	CHKDS 10 50 34.50

FEED THROUGH TERMINALS (KUT Series)

KST 4UWS			KUT 6			KST 6WS			KUT 10			KUT 16		
6.7 mm (0.26 inch)			8 mm (0.31 Inch)			8 mm (0.31 inch)			10 mm (0.39 inch)			12 mm (0.47 inch)		
46.4 x 42.5 (1.83 x 1.67)			46.4 x 42.5 (1.83 x 1.67)			49.8 x 42.5 (1.96 x 1.67)			46.4 x 42.5 (1.83 x 1.67)			51 x 44.5 (2.01 x 1.75)		
4 sq mm			6 sq mm			6 sq mm			10 sq mm			16 sq mm		
0.5 sq mm - 4 sq mm			0.5 sq mm - 6 sq mm			0.5 sq mm - 6 sq mm			1.5 sq mm - 10 sq mm			6 sq mm - 16 sq mm		
0.5 sq mm - 6 sq mm			0.5 sq mm - 10 sq mm			0.5 sq mm - 10 sq mm			1.5 sq mm - 16 sq mm			6 sq mm - 25 sq mm		
12 mm			12 mm			12 mm			12 mm			15 mm		
2 screw clamp & 1 tapped hole for cross connection			2 screw clamp & 1 tapped hole for cross connection			2 screw clamp & 1 tapped hole for cross connection			2 screw clamp and 1 tapped hole for cross connection			2 screw clamp & 1 tapped hole for cross connection		
800 V/32A/4 sq mm/0.5 Nm 600 V/35 A/10-20 AWG/7 Lbln			800 V/41A/6 sq mm/0.8 Nm 600 V/50 A/8-20 AWG/14 Lbln			630 V/41A/6 sq mm/0.8 Nm 600 V/40 A/8-20 AWG/12 Lbln			800 V/57 A/10 sq mm/1.2 Nm 600 V/65 A/6-16 AWG/14 Lbln			800 V/76 A/16 sq mm/1.2 Nm 600 V/100 A/3-12 AWG/17 Lbln		
M3			M3.5			M3.5			M4			M4		
 			 			 			 			 		
														
CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG
KST 4U WS	100	1.28	KUT 6	100	1.51	KST 6 WS	100	1.60	KUT 10	100	2.07	KUT 16	100	2.70
KP X	100	0.31	KPX	100	0.31	KSP 6WS	100	0.52	KPX	100	0.31	KPY	100	0.37
KB X	100	0.46	KBX	100	0.46	KBX	100	0.43	KBX	100	0.46	KB Y	100	0.43
KBXF	100	0.54	KBXF	100	0.54	KBXF	100	0.54	KBXF	100	0.54	KBZF	100	0.75
UHDD	100	0.80	UHDD	100	0.80	UHDD	100	0.80	UHDD	100	0.80	UHDD	100	0.80
PCK	100	7.00	PCK	100	7.00	PCK	100	7.00	PCK	100	7.00	PCK	100	7.00
SCKN	100	0.80	SCKN	100	0.80	SCKN	100	0.80	SCKN	100	0.80	SCKN	100	0.80
SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94
SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63
SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64
CCLA 2.5 -2W	100	0.56	CCLA 6 -2W	100	0.58	CCLA 6 - 2W	100	0.58	CCLA 10-2W	100	0.76	CCLA 16 - 2W	100	0.83
CCLA 2.5 -3W	100	0.84	CCLA 6 - 3W	100	0.86	CCLA 6 - 3W	100	0.86	CCLA 10-3W	100	1.16	CCLA 16 - 3W	100	1.24
CCLA 2.5 -4W	50	0.56	CCLA 6 - 4W	50	0.58	CCLA 6 - 4W	50	0.58	CCLA 10-4W	50	0.78	CCLA 16 - 4W	50	0.83
CCLA 2.5 -5W	50	0.69	CCLA 6 - 5W	50	0.71	CCLA 6 - 5W	50	0.71	CCLA 10-5W	50	0.98	CCLA 16 - 5W	50	1.04
CCLA 2.5 -10W	25	0.69	CCLA 6 - 10W	25	0.72	CCLA 6 - 10W	25	0.72	CCLA 10-10W	25	0.98	--	--	--
PSL 2.5 -2W	100	0.06	PSL 6 - 2W	100	0.08	PSL 6 - 2W	100	0.08	PSL 10-2W	100	0.11	PSL 16 - 2W	100	0.20
PSL 2.5 -3W	100	0.09	PSL 6 - 3W	100	0.12	PSL 6 - 3W	100	0.12	PSL 10-3W	100	0.18	PSL 16 - 3W	100	0.30
PSL 2.5 -4W	100	0.13	PSL 6 - 4W	100	0.16	PSL 6 - 4W	100	0.16	PSL 10-4W	100	0.23	PSL 16 - 4W	100	0.40
PSL 2.5 -5W	100	0.15	PSL 6 - 5W	100	0.20	PSL 6 - 5W	100	0.20	PSL 10-5W	100	0.28	PSL 16 - 5W	100	0.50
PSL 2.5 -10W	100	0.26	PSL 6 - 10W	50	0.20	PSL 6 - 10W	50	0.20	PSL 10-10W	100	0.55	--	--	--
SSP2.5-6	100	0.27	SSP2.5 - 6	100	0.27	SSP2.5-6	100	0.27	SSP10-16	100	0.32	SSP10 -16	100	0.32
SLC 2.5-2W	100	0.23	SLC 6 -2W	100	0.27	SLC 6 -2W	100	0.27	--	--	--	--	--	--
SLC 2.5-3W	100	0.33	SLC 6 -3W	100	0.43	SLC 6 -3W	100	0.43	--	--	--	--	--	--
SLC 2.5-4W	100	0.47	SLC 6 -4W	100	0.59	SLC 6 -4W	100	0.59	--	--	--	--	--	--
SLC 2.5-5W	50	0.29	SLC 6 -5W	50	0.36	SLC 6 -5W	50	0.36	--	--	--	--	--	--
SLC 2.5-10W	50	0.57	SLC 6 -10W	50	0.75	SLC 6 -10W	50	0.75	--	--	--	--	--	--
RSL 2.5	100	0.05	RSL 6	100	0.06	RSL 6	100	0.06	RSL 10	100	0.11	RSL 16	100	0.16
LSR2.5-6	100	0.31	LSR 2.5-6	100	0.31	LSR 2.5-6	100	0.31	LSR 10-16	100	0.49	LSR 10-16	100	0.49
Label KN 6.5	100 Strips	0.10	Label KN 8	100 Strips	0.12	Label KN 8	100 Strips	0.12	Label KN 10	100 Strips	0.15	Label KN 10	100 Strips	0.15
WL 2.5	100	0.31	WL 6	100	0.32	WL 6	100	0.32	WL 10	100	0.42	WL 16	100	0.52
SCKNMLH	50	0.55	SCKNMLH	50	0.55	SCKNMLH	50	0.55	SCKNMLH	50	0.55	SCKNMLH	50	0.55
SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60
KST4UWS(G), KST4UWS(K) KST4UWS(R), KST4UWS(Y), KST4UWS(B) KST4UWS(BL), KST4UWS(GR)			KUT6(G), KUT6(K) KUT6(R), KUT6(Y), KUT6(B) KUT6(BL), KUT6(GR)			KST6WS(G), KST6WS(K) KST6WS(R), KST6WS(Y), KST6WS(B) KST6WS(BL), KST6WS(GR)			KUT10(G), KUT10(K) KUT10(R), KUT10(Y), KUT10(B) KUT10(BL), KUT10(GR)			KUT16(G), KUT16(K) KUT16(R), KUT16(Y), KUT16(B) KUT16(BL), KUT16(GR)		
CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36
CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36
CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34
CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50

FEED THROUGH TERMINALS (KUT Series)

DESCRIPTION		KUT 25			KUT 35			KUT 50			KUT 95			
TERMINAL PITCH		12 mm (0.47 inch)			17 mm (0.67 inch)			20.5 mm (0.81 inch)			25 mm (0.98 inch)			
HEIGHT x WIDTH in mm (Inch)		56 x 45 (2.2 x 1.77)			58 x 51 (2.28 x 2.01)			75.5 x 71 (2.97 x 2.8)			90.5 x 83 (3.56 x 3.27)			
RATED CROSS SECTION		25 sq mm			35 sq mm			50 sq mm			95 sq mm			
CONNECTION	Flexible	6 sq mm - 25 sq mm			10 sq mm - 35 sq mm			16 sq mm - 50 sq mm			25 sq mm - 95 sq mm			
POSSIBILITY	Rigid	6 sq mm - 25 sq mm			10 sq mm - 35 sq mm			16 sq mm - 70 sq mm			25 sq mm - 120 sq mm			
WIRE STRIPPING LENGTH		15 mm			17 mm			24 mm			33 mm			
TYPE OF CONNECTION		2 screw clamp & 1 tapped hole for cross connection			2 screw clamp & 1 tapped hole for cross connection			2 screw clamp & 1 tapped hole for cross connection			2 screw clamp			
RATINGS	IEC 60947-7-1	1000 V/101 A/25 sq mm/2.3 Nm			1000 V/125 A/35 sq mm/3 Nm			1000 V/150 A/50 sq mm/8 Nm			1000 V/232 A/95 sq mm/20 Nm			
	 	600 V/115 A/2-10 AWG/20 Lbln			600 V/140 A/1-14 AWG/38 Lbln			600 V/150 A, 2/0-6 AWG/60 Lbln			600 V/230 A, 4/0-2 AWG/160 Lbln			
SCREW SIZE		M5			M6			M6			M8			
		    			    			    			    			
		  			  			  			  			
		CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	
TERMINAL TYPE		KUT 25	50	1.83	KUT 35	50	2.94	KUT 50	10	1.27	KUT 95	10	2.23	
END PLATE		KB T	100	0.45	Not Required			Not Required			Not Required			
PARTITION PLATE WITHOUT FOOT		KB T	100	0.56	--	--	--	--	--	--	--	--	--	
PARTITION PLATE WITH FOOT		KBZF	100	0.75	KBZF	100	0.75	--	--	--	--	--	--	
SUPPORT FOR PROTECTION COVER		UHDD	100	0.80	UHDD	100	0.80	--	--	--	--	--	--	
PROTECTION COVER		PCK	100	7.00	PCK 3	100	7.00	--	--	--	--	--	--	
END CLAMPS		SCKN	100	0.80	SCKN	100	0.80	--	--	--	--	--	--	
		SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94	
		SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63	
		SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64	
SHORTING LINK ASSEMBLY		- 2 WAY	CCLA 25- 2W	100	0.83	CCLA 35K - 2W	50	0.60	CCLA 50 - 2W	50	2.00	--	--	
		- 3 WAY	CCLA 25- 3W	100	1.24	CCLA 35K - 3W	50	0.90	CCLA 50 - 3W	50	3.00	--	--	
		- 4 WAY	CCLA 25- 4W	50	0.83	CCLA 35K - 4W	25	0.60	--	--	--	--	--	
		- 5 WAY	CCLA 25- 5W	50	1.04	CCLA 35K - 5W	25	0.38	--	--	--	--	--	
		- 10 WAY	--	--	--	--	--	--	--	--	--	--	--	
PERMANENT SHORTING LINK		- 2 WAY	PSL 16 - 2W	100	0.20	PSL 35K - 2W	100	0.28	--	--	--	--	--	
		- 3 WAY	PSL 16 - 3W	100	0.30	PSL 35K - 3W	100	0.42	--	--	--	--	--	
		- 4 WAY	PSL 16 - 4W	100	0.40	PSL 35K - 4W	100	0.56	--	--	--	--	--	
		- 5 WAY	PSL 16 - 5W	50	0.25	PSL 35K - 5W	50	0.35	--	--	--	--	--	
		- 10 WAY	--	--	--	--	--	--	--	--	--	--	--	
STUD FOR PERMANENT SHORTING LINK		SSP 10-16	100	0.32	SSP 35	100	0.55	--	--	--	--	--	--	
COMB LINK		- 2 WAY	--	--	--	--	--	--	--	--	--	--	--	
		- 3 WAY	--	--	--	--	--	--	--	--	--	--	--	
		- 4 WAY	--	--	--	--	--	--	--	--	--	--	--	
		- 5 WAY	--	--	--	--	--	--	--	--	--	--	--	
		- 10 WAY	--	--	--	--	--	--	--	--	--	--	--	
REMOVABLE SHORTING LINK		RSL 25	100	0.22	RSL 35K	100	0.25	--	--	--	--	--	--	
STUD FOR REMOVABLE SHORTING LINK		LSR 10-16	100	0.49	LSR 35K	100	0.80	--	--	--	--	--	--	
MARKING LABEL			Label KN 10	100 Strips	0.15	Label KN 10	100 Strips	0.15	Label KN 10	100 Strips	0.15	Label KN 10	100 Strips	0.15
WARNING LABEL			WL 16	100	0.52	WL 35	50	0.30	--	--	--	--	--	--
GROUP MARKING CARRIER		 	SCKNMLH	50	0.55	SCKNMLH	50	0.55	--	--	--	--	--	--
			SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60
COLOUR:		 GREY, KHAKHI	KUT25(G), KUT25(K)		 KUT35(G), KUT35(K)		KUT50(G), KUT50(K)		 KUT95(G), KUT95(K)					
		 RED, YELLOW, BLUE	KUT25(R), KUT25(Y), KUT25(B)		 KUT35(R), KUT35(Y), KUT35(B)		KUT50(R), KUT50(Y), KUT50(B)		 KUT95(R), KUT95(Y), KUT95(B)					
		 BLACK, GREEN	KUT25(BL), KUT25(GR)		 KUT35(BL), KUT35(GR)		KUT50(BL), KUT50(GR)		 KUT95(BL), KUT95(GR)					
MOUNTING CHANNEL		CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	
		CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	
		CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	
		CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50	